



Part Number:TOP50

0.65mm[0.026inch] test pitch


Probe Specifications	
Minimum Center:	0.65mm[0.026inch]
Full Stroke:	1.50mm[0.059inch]
Recommended Stroke:	1.0mm[0.039inch]
Spring Force:	30g[1.058oz]@1.5mm.
Impedance:	180milliohms
Current:	0.5Amp
Temperature:	-55°C to 120°C [-67°F to 248°F]
Spring Life:	500K cycles
Diameter Tolerance:	±0.01mm[±0.39mil]
Length Tolerance:	±0.10mm[±3.93mil]
Straightness Tolerance:	0.05mm[±1.97mil]

Materials Specifications	
Plunger:	BeCu or SK4, Rhodanizing
Spring:	Stainless Steel
Barrel:	Phosphor Copper,Au plating treatment




Probe mm.[inch]


Receptacle mm.[inch]



Fixture Drilling Measurement



Tip Style



How to order

TOP	50	F	025	30G
Series Name TOP=Normal ICT Probe CTOP=High Current Probe BP=Battery Probe FTOP=Frequency Probe ATOP=Automotive Probe SWTOP=Switch Probe	Test Pitch Number 50=PCB Test Probe Test pitch=0.65mm	Head Style Code F=30° tip angle C=Round more...	Head Diameter 025=0.25mm=0.010inch	Spring Force 30G=30grams=0.3Newton